



TPD-01-BT

HALE[®]
electronic

The future in taxi.

Bluetooth printer TPD-01-BT

Mobilize your business

TPD-01-BT

Bluetooth connectivity



Mobilize your printer with bluetooth!

- ▶ The multifunctional thermal paper printer TPD-01 now comes with a bluetooth interface
- ▶ Mobilize your business and print additional information from your mobile device onto your taximeter printer
- ▶ Easy implementation
- ▶ For Android operated Smartphones or Tablets
- ▶ Comes with Android libraries and demo program
- ▶ Existing printers are simply upgraded by a software update and exchange of the printed circuit board for keypad.

TPD-01-BT prints out:

- ▶ Trip receipts
- ▶ Shift accountings
- ▶ Trip memory
- ▶ Utilisation figures
- ▶ or any data from your android application

Various mounting possibilities:

- ▶ 3 different mounting versions for the paper roll: upside, backwards or completely on the back side
- ▶ Various mounting possibilities of the printer itself: velcro mounting, mounting bracket 90° or 30°
- ▶ For Mercedes Benz E211 and E212 mounting holder instead of ash-tray

Convincing Technology

Low current consumption corresponds to the automotive standards. The HALE TPD-01-BT consumes current only during printing (automatic wake-up via interface) and is otherwise in sleep mode.




Printer also available with magnetic card reader

Technical data

Dimensions	115 x 57 x 30 mm [4.53 x 224 x 1.18 inch] [W x H x D]
Weight	180 g
Operating voltage	8-18 V
Current consumption	<ul style="list-style-type: none"> • typ. 2 mA in stand-by [< 7 mA with bluetooth] • typ. 350 A in sleep mode with CAN operation [< 5 mA with bluetooth] • max. 1.5 A with 12V
Temperature	<ul style="list-style-type: none"> • -25°C to $+85^{\circ}\text{C}$, -13°F to $+185^{\circ}\text{F}$ (stock) • -10°C to $+70^{\circ}\text{C}$, $+14^{\circ}\text{F}$ to $+158^{\circ}\text{F}$ (operation)
Resolution	300 dpi, 28 characters / line
Graphics	32 kB bitmaps
Fast print	up to 4 cm, 1.58 inch / sec.
Special features	<ul style="list-style-type: none"> • 3-coloured status LED • autosleep and wake-up • end of paper detection • printer hed protection • 2 operating keys
Interfaces	<ul style="list-style-type: none"> • Bluetooth class 2 • RS 232 [5V] for Microtax®-05, WSZ-05 • interfaces for connection of data dispatching devices and credit card terminals • baud rates 300/1200/9600 baud [opt. 4800 baud] • HALE CAN for Microtax®-06, SPT-01, SPT-02 • opt. or integrated magnetic card reader

Approvals



The future in taxi.

HALE electronic GmbH
Eugen-Müller-Straße 18
A-5020 Salzburg

T: +43-662/439011-0
E: marketing@hale.at
www.hale.at